(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 25 November 2004 (25.11.2004)

PCT

(10) International Publication Number WO 2004/102720 A1

(51) International Patent Classification⁷: H10M 8/00

H01M 8/04,

(21) International Application Number:

PCT/JP2004/006664

(22) International Filing Date:

12 May 2004 (12.05.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-137801

15 May 2003 (15.05.2003)

(71) Applicant (for all designated States except US): NISSAN MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kanagawa-ku, Yokohama-shi, Kanagawa 2210023 (JP).


- (72) Inventor; and
- (75) Inventor/Applicant (for US only): ASO, Takeshi [JP/JP].

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the



warmed-up, a controller (8) serves for raising a temperature (Ts) of the stack when a possible generation (Gp) of power is reduced and for raising a temperature (Tb) of the battery when a possible charge (Cp) of power or a possible discharge (Dp) of power is reduced, to maintain stable power supply to the load even under a continued low-output condition.

